





## Aluminium Type XL-Z



Type XL



Type Z

Round strand rope with Steel core - metallic area C up to 0,487				Ferrules		
Rope Ø measured 1770 N/mm <sup>2</sup> grade		Rope Ø measured 1960 N/mm <sup>2</sup> grade		Ferrule No.	Pressed XL Ferrule Dimensions Ø mm	Tolerance mm
min.	max.	min.	max.			
46,3	50,7	45,6	48,9	XL 52	100	+2,1
50,8	54,3	49	51,5	XL 54	108	+2,3
54,4	58,2	51,6	55,8	XL 56	116	+2,4
58,3	61,9	55,9	59,2	XL 60	124	+2,5
62	65,8	59,3	63,4	XL 64	132	+2,6
65,9	69,7	63,5	66,9	XL 68	140	+2,8
69,8	73,6	67	71,2	XL 72	148	+3,0
73,7	77,4	71,3	74,5	XL 76	156	+3,2
77,5	81,3	74,6	78,8	XL 80	164	+3,3
81,4	85,2	78,9	82,1	XL 84	172	+3,5
89,2	93,1	86,6	90,1	XL 90	188	+3,8
		90,2	95,1	Z 94	190	+3,8
		95,2	101,5	Z 102	212	+3,8
		101,6	106,8	Z 102	214	+3,8

For accommodation of steel wire ropes with a higher tensile grade than 1960 N/mm<sup>2</sup> please refer to our technical department.